

<b>Sl No</b>	<b>Feature</b>	<b>Neutral Spec</b>	<b>Name &amp; Model No. of product offered</b>	<b>Compliance</b>	<b>Variation</b>
				<b>Yes/No</b>	
1	Display	Min.43" 4K UHD Display along with Kiosk enclosure with the following specifications, IPS/VA panel technology, Brightness: Min.500 cd/m2, Resolution: Min.3840 x 2160, Contrast Ratio (static): Min.1100:1, Viewing Angle: 178° (H) x 178° (V), Audio: In-built Speakers			
2	Operating hours:	24/7			
3	Orientation	Shall support both landscape and portrait			
4	Connectivity	Min. 2xHDMI In, 1xDP In, 1xDVI-D In, 1xUSB, 1xAudio In, 1xAudio Out, 1XDP/HDMI Out, Controls: RS232, Ethernet, IR, WiFi			
5	Features	Internal Media Player, Internal memory: 8GB, Built-in Wi-Fi, Screen Sharing feature, Web Browser			
6	Certification	UL, FCC,CE, Energy Star			
7	Signage Software Features	Lifetime license with following features-Grouping of displays / Admin rights for Content creation, content editing, content scheduling, Control all the displays centrally for Power ON/OFF over IP Network, Supports .mkv, .mpeg, .avi, .mpg, .mp4, .wmv, .mp3, .tiff, .bpm, .pptx, .pdf, .jpeg etc file formats, Sends emergency messages on any individual display or all the displays simultaneously over IP Network, Import, edit and schedule content minute, hour or day wise operation, Holiday			

		scheduling for Public Holiday & Sundays (the display will remain OFF on these days)			
8	Enclosure	Alluminium alloy black color with cutouts for easy access to ports and closing the when unused			
9	Form factor	Tablet Model			
10	Front Panel	Toughened Glass			
12	Cables	1.5m patch cord shall be included .Only power cable slot shall be found outside the unit. All other cables shall be neatly cable tied and secured from rat bites.			
13	Power Supply	230V, 50 Hz AC Supply.			
14	Base Plate Mounting	Should be strong enough to hold the weight and shall support mounting either fixed on floor or shall support wheels as per site requirement			
15	Language Support	English, Malayalam, Hindi, Tamil & Kannada			
16	Manageability	Should be manageable centrally through IP or URL as per signage software provided by supplier. Sample will be tested and verified.			
17	Warranty	5 Years OEM warranty for display			
<p>Note: Companies have to submit a sample piece to SHA Kerala head office at Thaycud, TVM for technical evaluation which can be returned after bidder selection. L1's model will be retained.</p>					